

252 Ritz

| Product Description | Standard | Product Data |
|--|---------------------|-----------------------------|
| Struktur – Structure – Struktur – Structure | ISO 2424 | Graphic cut pile |
| Gauge – Gauge – Teilung – Jauge | ISO 2424 | 1/8" |
| Luvmateriale – Pile material – Faser – Couche d'usage | DIR 96/73, 96/74 | 80/20 wool/nylon |
| Farvning – Dyeing – Färbung – Teinture | - | Pre-dyed |
| Bagside – Backing – Rücken – Dossier | hctl | Laminated Textile (LTB) |
| Bredde – Dimensions – Dimensionen – Dimensions | ISO 3018 | 400 cm |
| Luvhøjde – Pile height – Polhöhe – Epaisseur du velours | ISO 1766 | 6.0 mm |
| Total højde – Total height – Gesamthöhe – Epaisseur totale | ISO 1765 | 9.0 mm |
| Luvvægt – Pile weight – Polgewicht – Poids de velours | ISO 8543 | 1,300 g/m2 |
| Totalvægt – Total weight – Gesamtgewicht – Masse totale | ISO 8543 | 1,800 g/m2 |
| Noppeantal – Tufts – Noppenanzahl – Nombre de boucles | ISO 1763 | 127,575 tufts/m2 |
| Brugsområder – Performance areas – Anwendungsbereiche – Domaines d'usage | EN 1307 | Class 32 - General contract |
| Antistatiske egenskaber – Static control – Antistatausrüstung – Propriétés antistatiques | hctl | Permanent antistatic |
| Trappeegnet – Suitable for stairs – Treppeneignung – Aptitude escaliers | EN 1963 | Yes |
| Rullehjulsegnet – Suitable for castor chairs – Stuhlrolleneignung – Apte aux sièges à roulettes | EN 985 | No |
| Trinlydsdæmpning – Impact sound insulation – Trittschallschutz – Isolation phonique | ISO 10140 | 39 dB |
| Lysægted – Colorfastness to light – Lichtechtheit – Solidité de lumière | ISO 105 – B02 | 5 (pastel shade 4) |
| Vandægted – Colorfastness to water – Wassereichtheit – Solidité à l'eau | ISO 105 – E01 | 3 |
| Gnidægted våd/tør – Colorfastness wet/dry – Reibechtheit nass/trocken – Solidité au frottement humide/sec | ISO 105 – X12 | 3/4 |
| Brand – Fire Classification – Brandverhalten – Classement feu | EN 13501 – 1 IMO | Cfl – S1 Certified |
| EC Standard | EN14041 | Certified |
| Garanti mod gennemslid – Guarantee against wear – Garantie gegen Verschleiß – Garantie contre l'usure | hctl | 5 years |

hctl = Internal test from Hammer Carpets test laboratory. Due to ongoing development of products above declarations may change without prior notification

