

## 650 Emma

| Product Description  | Standard         | Product Data              |
|--|------------------|---------------------------|
| Struktur – Structure – Struktur – Structure  | ISO 2424         | Flatweave                 |
| Gauge – Gauge – Teilung – Jauge  | ISO 2424         | -                         |
| Luvmateriale – Pile material – Faser – Couche d'usage  | DIR 96/73, 96/74 | 100% Stone Fibre (PP)     |
| Farvning – Dyeing – Färbung – Teinture   | -                | Pre dyed                  |
| Bagside – Backing – Rücken – Dossier   | hctl             | Foam                      |
| Bredde – Dimensions – Dimensionen – Dimensions   | ISO 3018         | 400 cm/500 cm             |
| Luvhøjde – Pile height – Polhöhe – Epaisseur du velours  | ISO 1766         | 2.0-3.0 mm                |
| Total højde – Total height – Gesamthöhe – Epaisseur totale   | ISO 1765         | 5.0-6.0 mm                |
| Luvvægt – Pile weight – Polgewicht – Poids de velours  | ISO 8543         | 650 g/m2                  |
| Totalvægt – Total weight – Gesamtgewicht – Masse totale  | ISO 8543         | 2,200 g/m2                |
| Brugsområder – Performance areas –<br>Anwendungsbereiche – Domaines d'usage                              | EN 1307          | Class 23 - Domestic heavy |
| Antistatiske egenskaber – Static control –<br>Antistatausrüstung – Propriétés antistatiques              | hctl             | Permanent antistatic      |
| Trappeegnet – Suitable for stairs – Treppeneignung – Aptitude escaliers                                  | EN 1963          | Yes                       |
| Rullehjulsegnet – Suitable for castor chairs –<br>Stuhlrolleneignung – Apte aux sièges à roulettes       | EN 985           | No                        |
| Trinlydsdæmpning – Impact sound insulation –<br>Trittschallschutz – Isolation phonique                   | ISO 10140        | 24 dB                     |
| Brand – Fire Classification – Brandverhalten – Classement feu  | EN 13501 – 1     | Efl                       |
| EC Standard  | EN14041          | Certified                 |
| Garanti mod gennemslid – Guarantee against wear –<br>Garantie gegen Verschleiß – Garantie contre l'usure | hctl             | 5 years                   |

hctl = Internal test from Hammer Carpets test laboratory. Due to ongoing development of products above declarations may change without prior notification

